Mercedes

Actros 2636K 6x4 AMV manlift working

platform rolling rig tunnel T8-T12

GENERAL

ID number	M368953
Brand	Mercedes
Туре	Actros 2636K 6x4 AMV manlift working platform rolling rig tunnel T8-T12
Chassis number	WDB9321431L368953
1st Registration Date	20-11-2008
Mileage (Km)	20450
Country of registration	NO
Dimensions	1030x255x370

POWERTRAIN

Engine type	11.946 Liter Euro4
Gearbox type	Semi-automatic
Number of gears	16
Euro standard	4
Differential lock	×
ABS	×

CHASSIS

Empty weight	21275
Gross Combined Weight	60000
Gross weight	27500
Wheelbase	390 (1-2) + 145 (2-3)
Chassis height	140
Fuel Capacity	520 L






















TYRES

Remote control

extensions

Number of support legs

Number of hydraulic

Tyre size axle 1	315/80R22.5
Tyre size axle 2	315/80R22.5
Tyre size axle 3	315/80R22.5
AXLES Number of axles	3
Number of driven axles	2
Configuration	6x4
Suspension axle 1	Steel suspension
Suspension axle 2	Steel suspension
Suspension axle 3	Steel suspension
CABIN Cabin Type	Day cabin
Airconditioning	×
CRANE Brand crane	AMV
Type crane	T8-T12 tunnel working platform
Year of manufacture	2008
Maximum crane length	10.6m

4

1

ADDITIONAL INFO

AMV (Andersens Mek. Verksted AS) work platform for T8-T12 tunnel profile construction works, Year of manufacture 2008, Max. load 600 kg, Serial no. 4-3112, Radio remote control, Max. boom extension height 10.6m, Max. boom extension side 9.88m, Boom lift angle: -30 to +58 degrees, Boom swing: 120 degrees, Platform dim.: 5.5mx2.0m, Platform rotation: 135 degrees, Platform displacement: 3.0m, Platform tilt: 0-90 degrees, 4 Support legs, 55Kw hydraulic pump with both auxiliary drive and electromotor for boom / Compressor operation, Diesel powered generator 8.8KW, 690V/50HZ, Electric outputs 230v (2x 1 fase,1x 3 fase), Compressor 2.5 cbm, 7.0 bar // Truck: Euro4, Adblue, Steel suspension, Recodrive hydraulic drive and steering, Front tyres 385/65R22.5, Rear tyres 315/80R22.5, Semi-automatic EPS gearbox (3 pedals), Day cabin, Digital tacho, Shipment dimensions: 1030x255x370